

Zerogen[®] 100 SVT

MAGNESIUM HYDROXIDE

DESCRIPTION

Zerogen[®] magnesium hydroxide products provide excellent fire retarding and smoke suppression performance for the thermoplastic and elastomeric compounds. The Zerogen 100 SVT products are characterized by high chemical purity thus suitable for use in the compound applications where excellent electrical properties are needed, such as in cable insulation materials. Zerogen 100 SVT is an ultrafine particle size magnesium hydroxide with a proprietary surface treatment that provides superior fire performance when used to make fire-rated EVA compounds. The proprietary surface treatment improves smoke suppression efficiency of magnesium hydroxide and increases limiting oxygen index (LOI) of the EVA compound. As a result, lower magnesium hydroxide loading level can be used leading to enhanced rheological and processing performance, and improved compound mechanical properties. The surface treatment also promotes compatibility of the magnesium hydroxide with the polymer and high quality of dispersion.

GENERAL PHYSICAL AND CHEMICAL PROPERTY DATA

Physical Property	Unit	Typical Value
Specific Gravity	g/cm ³	2.4
Color		White
Refractive Index		1.58
Hardness	Mohs	2.5
325 Mesh Residue	%	≤0.5
Median Particle Size	Microns	0.8
Specific Surface Area (BET)	m ² /g	5
Free Moisture @ 105°C	%	≤0.1

Chemical Property	Unit	Typical Value
Magnesium Hydroxide, Mg(OH) ₂	%	≥99.5 (untreated base)
Calcium	%	≤0.02
Chloride	%	≤0.02
Iron	%	≤0.005
Loss on Ignition (1200°C)	%	≥31 (untreated base)

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Refer to Huber's Standard Conditions of Sale for the only express warranties applicable to the Huber products. Products incorporating Huber products are not warranted by Huber. In no event is Huber liable for consequential damages.